



INSTALLATION

UNIVERSAL DRINK HOLDER

1462

FITS: UNIVERSAL FOR CLUTCH OR BRAKE PERCH MOUNTING BOLTS VERTICAL SPACING CENTER TO CENTER AT 1-1/8" TO 1-11/16" APART TO ACCEPT INCLUDED M6 X 1 OR 1/4-20 BOLTS.

HONDA: ALL GL1500/1800 MODELS, ALL VTX1300/1800 MODELS, SHADOW 750 AERO, ACE & SPIRIT, SHADOW 1100

KAWASAKI: ALL VULCAN 900 MODELS, VULCAN 1500/1600 INCLUDING MEAN STREAK, ALL VULCAN 2000

SUZUKI: BOULEVARD M/C 50/C90/M109

YAMAHA: ALL ROAD STAR & WARRIOR MODELS, ALL V STAR MODELS, ALL VENTURE MODELS

HARLEY-DAVIDSON: ALL MODELS, 1982 & UP

NOTE: Universal Basket Holder will accept most average sized cups, cans, bottles, and mugs with a 2" to 3 1/2" diameter.

PARTS INCLUDED

- 1 Drink Holder Basket
- 1 Perch Mount Arm
- 1 Anti-Seize Packet
- 1 Perch Mount Kit
- 2 1/4-20 x 2" Button Socket Cap Screws
- 2 1/4-20 x 2-1/4" Button Socket Cap Screws
- 2 M6 x 1.0 x 55mm Button Socket Cap Screws
- 2 Washers
- 2 Spacers
- 1 Hardware Kit
- 2 Shims
- 1 Thumb Nut
- 1 5/16" Split Lock Washer
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.

WARNING! THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION! This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

ATTENTION! This indication alerts you to the fact that ignoring the contents described herein may negatively affect product performance and functionality.

TOOLS SUGGESTED

Set of Hex Wrenches

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Küryakyn warrants that any Küryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Küryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
 - The product must be properly installed, maintained and operated under normal conditions.
- Küryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Küryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Küryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Küryakyn and a customer.
- Küryakyn products are often intended for use in specific applications. Küryakyn makes no warranty if a Küryakyn product is used in applications other than intended.
- Küryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Küryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Küryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Küryakyn. Küryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Küryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Küryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Küryakyn USA® All Rights reserved.



kuryakyn.com

-cont.-

STRICTLY OBSERVE THE FOLLOWING GUIDELINES IN ORDER TO USE THE PRODUCT PROPERLY AND AVOID POTENTIALLY DANGEROUS ACCIDENTS.

PROCEDURE - Please note that all hardware included may not be used for installation!

NOTE Universal Basket Holder accepts most average sized cups, cans, bottles, and mugs with a 2" to 3.5" diameter.

STEP 1 Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface; turn off the ignition and allow the engine to cool.

STEP 2 Place a clean, soft blanket over the gas tank to protect the paint.

CAUTION! Avoid damage to the motorcycle. Protect painted surfaces with a soft cloth or blanket.

WARNING! ENSURE THAT THERE IS CLEARANCE AT ALL POINTS WHEN THE HANDLEBARS ARE TURNED, INSUFFICIENT CLEARANCE MAY CAUSE DAMAGE TO THE MOTORCYCLE OR CAN CAUSE LOSS OF CONTROL THAT COULD RESULT IN SEVERE INJURY OR DEATH.

STEP 3 As shown in PIC 1, remove the bottom screw securing the clutch perch halves; this screw will not be used again.

STEP 4 Identify the correct screw in the kit, either the metric or standard, by comparing threads on the included screws to the threads from the screw that was removed (the long 1/4-20 screws are generally used in older H-D motorcycles.)

STEP 5 As shown in PIC 2 Place the washer over the screw, then insert through the perch mount arm and place the spacer over the screw. Add Anti-Seize to the screw.

STEP 6 As shown in PIC 3, place the arm, screw, washer and spacer on the perch and start the screw. Finger tighten the screw for now.

STEP 7 Remove the upper screw securing the perch mounting halves; it will not be used again.

STEP 8 Rotate the arm up into position and install the new screw, washer and spacer in the same order as in PIC 2. Add Anti-Seize to the screw.

STEP 9 Tighten both of the screws securing the arm.

STEP 10 To mount the Universal Drink Holder, place the stud through the mounting arm, place one of the shims and the flat washer over the protruding end (PIC 4). Apply anti-seize to the threaded portion of the stud and secure with the thumb nut.

STEP 11 Turn the handlebars in both directions to their full stop position and ensure that there is clearance between the Universal Drink Holder and the gas tank, dash and other accessories.

STEP 12 Tighten all hardware.

CAUTION! Do not overload the Drink Holder with excessive weight.

ATTENTION! It is the installer's responsibility to ensure that all of the fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

CAUTION! Kuryakyn is not responsible for items that may be stolen or damaged in relation to the use of this product.

CAUTION! The adjustability of the Drink Holder was not intended to prevent spills.

Ride On!

Kuryakyn[®]

PIC. 1



PIC. 2



PIC. 3



PIC. 4



PAGE

2

UNIVERSAL DRINK HOLDER

INSTALLATION