



# INSTALLATION

## CURVED SIDE MOUNT LICENSE HOLDER 3173

FITS ALL '80-'05 DYNA AND '86-UP XL MODELS; ACCEPTS ALL 4"x7" LICENSE PLATES

### PARTS INCLUDED

- 1 Lighted Curved Vertical Side Mount License Holder
- 1 Dyna Swingarm Clamp Assembly, 2"
- 1 Sportster Swingarm Clamp Assembly, 1.5"
- 1 5/16-18 x 3/4" SHCS Fastener
- 1 Wiring Kit, including:
- 4 Cable Tie, 4" Black
- 1 Dielectric Grease
- 4 T-Tap Female Quick Slide Scotch-Lock Connectors
- 4 Male Scotch-Lock Connectors
- 1 1" x 3" x 0.100" Single-Side Adhesive Pad
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KÜRYAKYN!

### TOOLS SUGGESTED

Allen wrenches, terminal crimpers.

**ATTENTION!** A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all steps in the procedure; consult a trained technician.

**ATTENTION!** When routing the wiring harness, be sure to keep the wiring away from any moving parts. Kuryakyn **WILL NOT** warranty any lighted license plate that fails due to pinched, crimped, broken, abraded, or frayed wires.

**NOTE** It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

### PROCEDURE

**STEP 1** Determine which swingarm clamp you will need. For Dyna models, use the 2" clamp; for XL models, use the 1.5" clamp. Install the appropriate clamp over the swingarm and tighten the fasteners. See **PIC.1**. Be sure the clamp does not interfere with any moving parts.

-cont.-



### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



**STEP 2** Thread the wiring harness on the license plate frame through the wire channel and port on the back plate. See [PIC.2](#).

**STEP 3** Remove the paper backing from the self-adhesive pad and place the adhesive pad on the backing plate; this will help eliminate excess vibration.

**STEP 4** Place your license plate into the license plate frame and secure it to the back plate with the supplied fasteners. See [PIC.3](#).

**STEP 5** Loosely mount the license plate assembly to the clamp on the swingarm using the supplied fastener. Adjust the angle of the license plate assembly for best visibility. Secure the fastener. See [PIC.4](#).

**STEP 6** Remove the seat to access the stock wiring connections. Refer to your factory service manual for specific instructions. See [PIC.5](#).

**STEP 7** Route the license plate wiring harness along the swingarm and up under the seat to the stock wiring connections. Be sure the wiring harness will not come in contact with any moving parts; Küryakyn will not warranty lighted license plates that fail due to pinched, crimped, broken, abraded, or frayed wires. Secure the wiring harness along the swingarm with the supplied cable ties.

**STEP 8** Use a terminal crimper to install the male terminal ends on the stripped ends of the license plate wiring harness. See [PIC.6](#). The center conductor of the wire must be in the metal sleeve of the terminal end. Do not crimp the insulation of the wire.

**ATTENTION!** The following two photos show a red wire. The wire color for your particular model may be different. Verify the correct wire function by either using a test light or referring to your factory service manual.

**STEP 9** Use a test light to identify the "Run" power wire and ground wire on the bike. Install a Scotch Lock connector on each wire. Place the wire into the metal conductor tabs as shown in [PIC.7](#). Fold the cover down and squeeze until the locking tab snaps into place.

-cont.-

# Küryakyn

PIC.2



PIC.3



PIC.4




PIC.5



PIC.6



PIC.7



PAGE

2

**CURVED SIDE MNT LICENSE HOLDER**


**INSTALLATION**

**STEP 10** Install the male terminal ends from the license plate wiring harness to the Scotch Lock connectors. The red wire connects to the "Run" power wire; the black wire connects to the ground wire. See PIC.8. Be sure to use the supplied dielectric grease on the terminal connections.

**STEP 11** Turn on the ignition and check that the license plate light illuminates when the "Run" lights are on. Replace the seat. Be sure all fasteners are secure before riding.

*Ride On!*

**PIC.8**



**PIC.9**

