



INSTALLATION

GRAN-THROOVER SADDLEBAGS 4171

FITS MOST MODELS

PART #	INCLUDED
	1 Saddlebags, pair
	2 Velcro Strap w/Clip
604144A	4 Adjustable Strap
404141L	1 Cable Lock
304171	1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

CAUTION! Prevent potential serious injuries! Be sure all fasteners are secure before riding.

WARNING! PREVENT SERIOUS INJURIES AND/OR DEATH! NEVER EXCEED THE MANUFACTURER'S RECOMMENDED LOADING LIMITS FOR YOUR MOTORCYCLE! BE SURE THE SADDLEBAGS DO NOT COME INTO CONTACT WITH ANY MOVING PARTS. ALWAYS CHECK FOR PROPER CLEARANCE BEFORE RIDING!

RECOMMENDATIONS

- The saddlebags fit either over or under the passenger seat, see PIC.1 and PIC.2. The saddlebags can be positioned with the narrow wedge end facing either forward or backward, depending on the best fit for your application.

PIC.2



PIC.1



- Use the adjustable straps and the Velcro clip straps to secure the saddlebags to your motorcycle. Kuryakyn recommends securing the saddlebag to the passenger footpeg, or the frame. DO NOT secure the saddlebags to the swingarm or any other part that moves independently from the seat. Be sure that the straps will not become tangled in any moving parts before riding.
- The width between the tops of the saddlebags is adjustable, allowing the bags to fit many applications, see PIC.3. Separate the Velcro flaps and reposition to adjust the width. Be sure that the width between the saddlebags is not so loose that a saddlebag could get caught under the fender or in the wheel. Always check for proper clearance before riding.

CUSTOMER SERVICE

877.370.3604 (toll free)

INSTALLATION QUESTIONS

techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



- The saddlebags are equipped with multiple steel D-rings allowing you to get the best fit for your application. Slide the steel D-rings into the elastic pockets when not in use to eliminate rattling due to vibration, see [PIC.3](#). Slide the cable lock through the D-rings to secure the saddlebags to your motorcycle, see [PIC.4](#).

WARNING! AFTER INSTALLING THE SADDLEBAGS, BE SURE TO CHECK FOR PROPER CLEARANCE BETWEEN THE BAG AND ANY MOVING PARTS, INCLUDING THE WHEELS AND SWING ARM. NEVER PLACE THE ANCHORING STRAPS NEAR THE WHEELS OR BRAKE CALIPERS. BE SURE THE PLACEMENT OF THE SADDLEBAGS DOES NOT INTERFERE WITH SAFE OPERATION OF THE MOTORCYCLE.

CAUTION! The saddlebags have heat-resistant shields but we do not recommend placing the bags near exhaust pipes. Be sure to maintain proper clearance away from exhaust pipes.

FEATURES

- The included rain gear stows in its own pocket at the narrow wedge end of each saddlebag. An expanding drink holder is also located on the narrow wedge end of each saddlebag, see [PIC.5](#).
- Each saddlebag has a large exterior side pocket and hidden expansion panels. Unzip the panels for more room inside the bags, see [PIC.6](#).
- Interior pockets make storing and finding small items easy. The top zippered flap also has both the interior and exterior pockets, see [PIC.7](#).

PIC.3

ELASTIC POCKETS FOR D-RINGS

ADJUSTABLE VELCRO FLAPS

PIC.4

CABLE LOCK

PIC.5

RAIN GEAR STOWS IN POCKET

EXPANDABLE DRINK HOLDER

PIC.6

EXPANSION PANEL

PIC.7

INTERIOR POCKETS

LARGE EXTERIOR POCKET

RETRACTABLE CABLE LOCK 404141L

STEP 1 See [PIC.8](#). To select a new combination for the lock, press button "A" and hold down. Push the cable end (labeled as "B") down/inward until you hear it click.

STEP 2 Choose your new combination by turning the three tumblers (labeled as "C") to a three-digit combination that you will remember. Then pull back up on the cable end to set your combination.

STEP 3 Press down on the "A" button to pull the cable end out. Plug the cable end into the cable lock receptacle (labeled as "D") until you hear it click into the locked position. If you have too much slack in the cable, press the "A" button to recoil the slack amount of cable. Turn the tumblers to a position that is NOT your chosen combination to lock the mechanism.

STEP 4 To unlock, turn the tumblers to your chosen combination and press the "E" button to release the cable and the "A" button to recoil the cable.

PIC.8



Ride On!