



INSTALLATION

TRIPLE WHAMMY RUN-TURN-BRAKE LIGHT KIT 4603

FOR YAMAHA

FITS ALL ROAD STAR 1600, ALL '98-'03 V-STAR 1100 & 650.

PARTS INCLUDED

- 1 Run-Turn-Brake Control Module
- 1 Flash Tab
- 1 Dielectric Grease
- 4 Cable Ties, Black Nylon
- 2 Red Colored Turn Signal Bulbs
- 2 Clear Turn Signal Lenses
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

THANK YOU FOR CHOOSING KÜRYAKYN!

IMPORTANT INFORMATION! PLEASE READ BEFORE STARTING INSTALLATION.

- The control module is compatible with motorcycles that have the rear lighting circuit wiring in stock configuration. If the motorcycle is already equipped with a Honda accessory control module or other aftermarket control module, remove it before installing the Run-Turn-Brake control module.
- The control module is compatible with stock rear single-circuit turn signals, as well as custom single-circuit lights and LEDs.
- Any existing load equalizers must be removed prior to installing the Run-Turn-Brake control module. Any load equalizers necessary after installation of the Run-Turn-Brake control module can be reinstalled later. NEVER install a load equalizer between the control module and the rear lights!
- The control module adds "Run", "Turn", and "Brake" function to stock rear single-circuit turn signals, as well as custom single-circuit lights and LEDs.

ATTENTION! The rear turn signals must be fit with the included clear lenses and red bulbs to meet State and Federal Regulations for rear running lights. Check with your local laws before re-using stock amber lenses or bulbs on any lights on the rear of the motorcycle.


ATTENTION! A factory service manual may be helpful in performing this installation. Do not attempt to perform this installation if you are not confident in your ability to complete all steps in the procedure; consult a trained technician.

PROCEDURE

STEP 1 Locate the rear fender lighting wiring harness under the seat. Refer to your factory service manual for help locating the wiring harness. See [PIC.1](#).

NOTE You may also follow the wires coming from the turn signals and taillight to under the seat.

-cont.-



CUSTOMER SERVICE
877.370.3604 (toll free)

INSTALLATION QUESTIONS
techsupport@kuryakyn.com
or call 715.247.2983

LIMITED WARRANTY
Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



STEP 2 Separate the two halves of the connector plugs. Install the Run-Turn-Brake control module inline; be sure to apply dielectric grease to the electrical connections before mating.

STEP 3 Remove the two screws in the the rear turn signal lenses; set the lenses aside, they will not be re-used.

STEP 4 Push the bulb into the socket and turn counterclockwise to remove; lift bulb out of the socket. Insert the new bulb into the socket.

STEP 5 Push the new red bulb straight into the socket and turn clockwise to secure. .

STEP 6 Install the clear turn signal lenses.

NOTE The Run-Turn-Brake control module is supplied with a flash tab. With flash tab installed, the brake light and turn signals will flash multiple times, then illuminate steady when the brake is applied. With the flash tab removed, the brake light and turn signals will illuminate steady when the brake is applied. Be sure the motorcycle ignition is in the "off" position before installing or removing the flash tab.

STEP 7 Start the motorcycle and test the function of the Run-Turn-Brake control module:

- A)** Verify the tail lamp and turn signals illuminate.
- B)** Apply the brake; if the flash tab is installed, verify the brake light and turn signals flash multiple times before illuminating steady. If the flash tab is not installed, verify the brake light and turn signals illuminate steady while the brake is activated.
- C)** Verify that when either of the turn signals are applied that they do not flash too rapidly or operate erratically. If this occurs, you will need to install a load equalizer. See the end of this document for the load equalizer installation procedure.

STEP 8 Stow the Run-Turn-Brake control module under the seat. If you will not be installing the load equalizer, replace the seat. If you will be installing the load equalizer, leave the seat off and proceed to the next section.

INSTALLING THE LOAD EQUALIZER

ATTENTION! Any load equalizers must be installed upstream of the Run-Turn-Brake control module. **NEVER** install a load equalizer between the Run-Turn-Brake control module and the rear lights.


STEP 9 The motorcycle must be "off" before installing the load equalizer. Locate the Run-Turn-Brake control module and plug the load equalizer into one of the empty 3-pin socket on the control module.

STEP 10 Start the motorcycle and retest the light functions, refer to STEP 4. If the lights still flash too rapidly or operate erratically, you will need to install a second load equalizer (Küryakyn P/N 4810, sold separately).

STEP 11 The load equalizers become warm during normal operation of the turn signals. Secure the load equalizer to the motorcycle frame; this will act as a heat sink and help cool the load equalizer. Keep the load equalizer away from any heat-sensitive components.

-cont.-

Küryakyn



PAGE
2

TRIPLE WHAMMY INSTALLATION

WARNING! ALWAYS INSTALL THE LOAD EQUALIZER UPSTREAM OF ANY EXISTING AFTERMARKET MULTIFUNCTION CONTROL MODULES. DO NOT INSTALL A LOAD EQUALIZER BETWEEN A MODULE AND THE TURN SIGNALS AS THIS WILL OVERLOAD THE MODULE. OVERLOADING WILL DAMAGE THE MODULE AND CREATE A FIRE HAZARD!

WARNING! LOAD EQUALIZERS GENERATE HEAT WHEN IN USE. AVOID USING THE TURN SIGNALS FOR AN EXTENDED PERIOD OF TIME, OTHERWISE THE LOAD EQUALIZER WILL OVERHEAT. NEVER OPERATE THE FOUR-WAY FLASHERS UNLESS YOU FIRST REMOVE THE LOAD EQUALIZER. OVERHEATING WILL DAMAGE THE LOAD EQUALIZER, CAUSING LOSS OF TURN SIGNAL OPERATION AND CREATES A FIRE HAZARD!

Ride On!

Kuryakyn

PAGE

3

TRIPLE WHAMMY INSTALLATION