



# INSTALLATION



## LUGGAGE RACK FOR GL1800 7151

PART #	INCLUDED
401033	1 Rack
401034	1 Rubber Rack Insert
907151	1 7151 Hardware Kit Including: 4 Cup washer 2 Rubber Spacer with Adhesive Back 8 Rubber washer 2 10-24 x 1" 2 10-24 x 1-1/4" 4 Flat washer - 1/4" zinc
307151	1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KURYAKYN!

### THIS RACK HAS A 5 LB SUGGESTED MAX LOAD CAPACITY

**PLEASE NOTE** It is the installers' responsibility to make sure all fasteners (including pre-assembled) are tightened before operation of motorcycle. Kuryakyn will not warranty components that are lost due to improper installation. Periodic maintenance may be required.

### PROCEDURE

**STEP 1** Place masking tape on the top (painted) surface of the tour box in the location of the luggage rack legs to prevent scratching.

**STEP 2** Set the luggage rack in position on top of the tour box, with the legs resting on the masking taped areas. While holding the rack centered where you want it, trace the location of the legs on to the masking tape. Carefully mark the very center of your tracings.

**STEP 3** Double check to be certain the rack is centered in the position you desire. Carefully drill a 1/4" hole at the center of the marked locations **AT THE REAR OF THE TOUR BOX ONLY!!** (Hint: You may wish to drill a small diameter pilot hole first. This will lessen the chance of the drill "walking" and harming the finish. While drilling the rear holes, try to match the angle of the rear mounting legs.) Each hole will penetrate the inner and outer surface of the tour box at the rear mounting points.

**STEP 4** Open the top of the tour box, and remove all fasteners that hold the inner surface of the box top in place. Remove the inner surface. Now drill the front two mounting holes as marked. Only the outer surface of the box will be drilled for the front two mounts. Remove the masking tape from around the front two holes. Mount the front half of the rack. The cupped washers will be inserted onto the feet of the luggage rack. The 10"-24 x 1" button head cap screws, one flat washer and two rubber washers will be used per bolt. A rubber washer will be placed on either side of the mounting surface and the metal washer next to the screw. Tighten these assemblies into the luggage racks front feet. Do not over tighten the fasteners.

-cont.-

### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

• Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).

• The product must be properly installed, maintained and operated under normal conditions.

• Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.

• Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.

• Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.

• Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.

• Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn™ product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA™ All Rights reserved.



**STEP 5** Mounting the rear half of the rack. Remove the masking tape from around the rear holes. One at a time, remove the adhesive backing from the spacers. On the inside of the top of the tour box affix the rubber spacers so their I.D.s are concentric with the I.D. of the holes you drilled in the top of the box. Reinstall the inner surface of the tour box in the same manner as it was removed. Mount the rear half of the rack in the same manner as you did with the front half, except the 10"-24 x 1-1/4" button head cap screws will be used here. Tighten the rear mounting bolts. (Easy does it!)

**Kuryakyn™**

*Ride On!*

**PAGE**

**2**

**LUGGAGE RACK FOR GL1800**

**INSTALLATION**