



# INSTALLATION



## RETRACTABLE PASSENGER PEGS 7926

**FITS: '93-'06 DRESSERS AND ROAD KINGS EQUIPPED WITH PASSENGER BOARDS (EX. '04-'06 FLHTCSE OR FLHTCUSE)**

### PARTS INCLUDED

- 1 Left Retractable Passenger Peg Assembly
- 1 Right Retractable Passenger Peg Assembly
- 2 Plastic Stop Pads
- 2 Small ISO Peg
- 1 Installation Instructions

*Please read and understand entire instructions before starting installation.*

### THANK YOU FOR CHOOSING KÜRYAKYN!

### NOTE

These assemblies are intended for use on '93-'06 STOCK H-D footboard mounts. This kit IS NOT compatible with H-D's "Adjustable Passenger Footboard Mounting Kit," Harley P/N 50789-99 or H-D's chrome passenger footboard support kit, P/N 52714-04.

**ATTENTION!** It is the installer's responsibility to ensure all fasteners (including pre-assembled) are tightened before operation of the motorcycle. Kuryakyn will not warranty components lost due to improper installation. Periodic maintenance may be required.

### PROCEDURE

**STEP 1** Be sure the stock footboard brackets are set in the mid position on the bike.

**STEP 2** Remove the lower clamp halves on the adjustable peg brackets.

**STEP 3** Establish the proper orientation of the assembly. When the adjustable arms are retracted, they should lay horizontally, extending toward the rear of the motorcycle. See PIC.1 and PIC.2. When they are deployed, they will angle up and toward the front of the bike. See PIC.3 and PIC.4. There are three screws on each clamp assembly. When the Retractable Pegs are installed on the appropriate side of the bike, the single 5/16" clamp screw will be forward of the stock footboard mount.

**STEP 4** Place the upper clamp and swing arm assembly on top of the stock footboard mount. Place the plastic stop pad on the lower clamp so that it is in the position shown in PIC.6. Install the corresponding lower clamp half, but do not tighten the bolts at this time. Slide the retractable peg assembly outward, away from the motorcycle as far as it will go. This should still allow the footboard to fold up completely. Tighten this assembly at this time. Keep the gap in the front and rear of the clamp equal — do not over tighten the clamp bolts! (10-14 ft/lbs for 1/4"-20 fasteners, 15-18 ft/lbs for 5/16"-18 fasteners.)

**STEP 5** Repeat the installation procedure on the opposite side of the bike.

**-cont-**

### CUSTOMER SERVICE

877.370.3604 (toll free)

### INSTALLATION QUESTIONS

techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA All Rights reserved.



**STEP 6** See [PIC.5](#). To adjust the pegs, retract the sliding bolt, and rotate it into the lock slot. Move the swing arm forward and backward to your approximate desired position and release the lock bolt. Move the swing arm front and rear until the lock bolt snaps into place. Re-engage the lock bolt.

## CAUTIONS

- 1) Do not attempt to adjust the position of the swing arms while the bike is in motion, or when the bike is running, or has been run recently. The exhaust pipes are extremely hot!
- 2) Do not stand on the retractable pegs – these are footrests only!!

*Ride On!*

PIC.1



PIC.2




PIC.3



PIC.4



PIC.6



PIC.5



PAGE

2