



## EZ SLIDER REAR WHEEL DOLLY 939

### UNIVERSAL FITMENT

### PARTS INCLUDED

- 1 EZ Slider Rear Wheel Dolly
- 1 Installation Instructions

Please read and understand entire instructions before starting installation.

### THANK YOU FOR CHOOSING KÜRYAKYN!

**IN ORDER TO PROTECT YOU AND OTHERS FROM POSSIBLE INJURY AND/OR PROPERTY DAMAGE OR LOSS, PLEASE PAY CLOSE ATTENTION TO ALL INSTRUCTIONS, WARNINGS, CAUTIONS AND ATTENTION NOTES REGARDING THE USE AND CARE OF THIS PRODUCT.**

**CAUTION!** This indication alerts you to the fact that ignoring the contents described herein can result in potential injury or material damage.

### PROCEDURE FOR SETTING HANDLE POSITION

- STEP 1** Unfold EZ Slider handle from the storage position or flat folded position by unlocking and removing the pin from the position selecting plate.
- STEP 2** Adjust the handle to the desired position to create proper leverage, as well as clearance for any saddlebags.
- STEP 3** Insert pin back through the position selecting plate as well as the handle.

### PROCEDURE FOR MOVING BIKE

**CAUTION!** Front wheel must be properly secured in wheel chock or front wheel clamp before attempting to move rear wheel.

- STEP 1** Place front wheel into wheel chock or other front wheel-clamping device.
- STEP 2** Make sure the front of the bike is properly secured.
- STEP 3** Roll the EZ Slider Dolly under the rear wheel from either side of the bike.
- STEP 4** Push down on the dolly handle to lift rear of the bike.
- STEP 5** Move to desired location. When satisfied with location, let up on the handle to lower the bike.
- STEP 6** Roll dolly out from the rear wheel. Remove pin from handle and fold the dolly flat for easy storage.

**CAUTION!** Failure to properly secure the front wheel could cause the bike to fall over when rear wheel is lifted causing personal injury or property damage.



**CUSTOMER SERVICE**  
877.370.3604 (toll free)

**INSTALLATION QUESTIONS**  
techsupport@kuryakyn.com  
or call 715.247.2983

### LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials and workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

- Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
- The product must be properly installed, maintained and operated under normal conditions.
- Kuryakyn makes no warranty, expressed or implied, with respect to any gold plated products.
- Kuryakyn shall not be liable for any consequential and incidental damages, including labor and paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn and a customer.
- Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
- Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. Components of Kuryakyn products containing L.E.D.s will be warranted for defects in materials and workmanship for 3 years from the date of purchase.
- Kuryakyn makes no warranty of any kind in regard to other manufacturer's products distributed by Kuryakyn. Kuryakyn will pass on all warranties made by the manufacturer and where possible, will expedite the claim on behalf of the customer, but ultimately, responsibility for disposition of the warranty claim lies with the manufacturer.

### ABOUT OUR CATALOG

You'll find all our innovations for H-D, GL and Metric Cruisers in our annual catalogs. Order online today—select the "CATALOGS" icon. Each Kuryakyn® product comes with a Proof-of-Purchase good for a complimentary catalog. Details in packaging.

Be sure to ask your local dealer about other Kuryakyn® products, the motorcycle parts and accessories designed for riders by riders.

©2005 Kuryakyn USA® All Rights reserved.

# Ride On!

