

INSTALLATION INSTRUCTIONS

FREE-FLEX DEVICE HOLDER, HANDLEBAR CLAMP SCREW MOUNT

6438

THANK YOU FOR CHOOSING KURYAKYN!

Protect yourself and others from possible injury and property damage or loss. Pay close attention to all instructions, warnings, cautions, and notices regarding the installation, use, and care of this product.

WARNING THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN POTENTIAL DEATH OR SERIOUS INJURY.

CAUTION THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN CAN RESULT IN MINOR OR MODERATE POTENTIAL INJURY.

NOTICE

THIS INDICATION ALERTS YOU TO THE FACT THAT IGNORING THE CONTENTS DESCRIBED HEREIN MAY NEGATIVELY AFFECT PRODUCT PERFORMANCE AND FUNCTIONALITY OR DAMAGE THE PRODUCT ITSELF OR THE PRODUCT TO WHICH IT IS BEING ATTACHED.

ENSURE THAT THE FOLLOWING PARTS HAVE BEEN INCLUDED IN THE KIT:

1	Device Holder	1	Device Holder Nut
1	Phone Retainment Device	1	Bolt Mount

YOU WILL ALSO NEED:

Socket bit set, ft-lbs (Nm) torque wrench, blue Loctite

NOTICE

THESE INSTALLATION INSTRUCTIONS CONTAIN IMPORTANT INFORMATION. ENSURE THE END USER RECEIVES THIS COPY AND IS AWARE OF ITS IMPORTANCE FOR FUTURE USE.

STEP 1

Read and understand all steps in the instructions before starting the installation. Park the motorcycle on a hard, level surface and turn off the ignition. Let motorcycle cool.

CAUTION

ENSURE THAT THE INSTALLATION OF THIS PRODUCT DOES NOT INTERFERE WITH THE PROPER OPERATION OF THE MOTORCYCLE BEFORE RIDING.

NOTICE

AVOID DAMAGE TO THE MOTORCYCLE. PROTECT PAINTED SURFACES WITH A SOFT CLOTH OR BLANKET.

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT THERE IS ADEQUATE CLEARANCE BETWEEN THE DEVICE HOLDER AND ANY PAINTED SURFACES. KURYAKYN IS NOT RESPONSIBLE FOR ANY DAMAGE DUE TO INADEQUATE CLEARANCE.

STEP 2

Place a clean, soft blanket over the gas tank to protect the paint.


STEP 3

Refer to PIC 2. Remove one of the bottom screws from the handlebar clamp. Set it aside, it will not be used again.

STEP 4

Locate provided Bolt Mount. Apply a small amount of blue Loctite to the threads of the bolt. Align and secure the bolt mount to the bottom mounting hole of the handlebar clamp on the motorcycle. Fully tighten the bolt.

TORQUE VALUE FOR HANDLEBAR CLAMP FASTENER:
9ft-lbs (12.20 Nm)



INSTALLATION INSTRUCTIONS

FREE-FLEX DEVICE HOLDER, HANDLEBAR CLAMP SCREW MOUNT

6438

-CONTINUED-

- STEP 5** Refer to PIC 3 and 4. Locate provided Device Holder Nut. Place the fastener onto the ball mount of the installed mount, the fastening side facing out towards the ball mount.

Note: Device Holder Nut might be located on the device holder's mounting base, or individually within the packaging it came in.

- STEP 6** Refer to PIC 5 and 6. On the back side of the Device Holder, align and place the two (2) small slots on the retainment device over the two tabs on the Device Holder. Align and place the bottom cutout of the retainment device over the mounting base of the Device Holder.

- STEP 7** Refer to PIC 7. Align and press the base of the Device Holder over the ball mount of the installed mount. Use the Device Holder Nut, located on the installed mount, to secure the assembly in place.

- STEP 8** Refer to PIC 8. Slide the phone into Device Holder's arms. Secure phone in place by pulling the corner cutouts of the Phone Retainment Device up and over the corners of the phone.

Note: Refer to PIC 9. For shorter phones, cut and remove the top cutouts of the Phone Retainment Device. Secure the phone in place by pulling the corner cutouts over the corners of the phone.

WARNING

ENSURE THAT THERE IS CLEARANCE AT ALL POINTS WHEN THE HANDLEBARS ARE TURNED, INSUFFICIENT CLEARANCE MAY CAUSE DAMAGE TO THE MOTORCYCLE OR CAN CAUSE LOSS OF CONTROL THAT COULD RESULT IN SEVERE INJURY OR DEATH.


WARNING

TO PREVENT POSSIBLE LOSS OF CONTROL, WHICH COULD RESULT IN A POSSIBLE INJURY OR DEATH, WE DO NOT RECOMMEND REMOVING AND REPLACING OBJECTS IN THE HOLDER WHILE RIDING THE MOTORCYCLE.

NOTICE

ENSURE THAT THE DEVICE HOLDER IS SECURE ON THE MOUNT AND THAT THE MOUNT IS SECURE ON THE MOTORCYCLE. KURYAKYN IS NOT RESPONSIBLE FOR ANY BELONGINGS THAT ARE STOLEN OR DAMAGED FROM USE OF THIS DEVICE HOLDER OR FROM THE DEVICE HOLDER OR MOUNT NOT BEING PROPERLY SECURED TO THE MOTORCYCLE. IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.


PIC 3
OFF VEHICLE
PHOTOS SHOWN



PIC 4



PIC 5



PIC 6



PIC 7




PIC 8



PIC 9

FOR SHORTER
PHONES ONLY



INSTALLATION INSTRUCTIONS

FREE-FLEX DEVICE HOLDER, HANDLEBAR CLAMP SCREW MOUNT

6438

-CONTINUED-

NOTICE

IT IS THE INSTALLER'S RESPONSIBILITY TO ENSURE THAT ALL OF THE FASTENERS (INCLUDING PRE-ASSEMBLED) ARE TIGHTENED BEFORE OPERATION OF THE MOTORCYCLE. KURYAKYN WILL NOT PROVIDE WARRANTY COVERAGE ON PRODUCTS OR COMPONENTS LOST DUE TO IMPROPER INSTALLATION OR LACK OF MAINTENANCE. PERIODIC INSPECTION AND MAINTENANCE ARE REQUIRED ON ALL FASTENERS.

LIMITED WARRANTY

Kuryakyn warrants that any Kuryakyn products sold hereunder, shall be free of defects in materials & workmanship for a period of one (1) year from the date of purchase by the consumer excepting the following provisions:

1. Kuryakyn shall have no obligation in the event the customer is unable to provide a receipt showing the date the customer purchased the product(s).
2. The product must be properly installed, maintained & operated under normal conditions.
3. Kuryakyn shall not be liable for any consequential & incidental damages, including labor & paint, resulting from failure of a Kuryakyn product, failure to deliver, delay in delivery, delivery in nonconforming condition, or for any breach of contract or duty between Kuryakyn & a customer.
4. Kuryakyn products are often intended for use in specific applications. Kuryakyn makes no warranty if a Kuryakyn product is used in applications other than intended.
5. Kuryakyn electrical products are warranted for one (1) year from the date of purchase by the consumer. L.E.D.'s contained in components of Kuryakyn products will be warranted for defects in materials & workmanship for 3 years from the date of purchase whereas all other components shall be warranted for one (1) year.
6. All warranty claims must be directed to the place of purchase. Merchandise sold through internet auction sites or any other unauthorized reseller shall not carry a Kuryakyn warranty. If unsure, please contact the place of purchase to verify they are an authorized Kuryakyn reseller.

RETURN POLICY

Merchandise determined to be defective may be returned up to one year from the date of purchase. Returns must be processed through original seller. Returned merchandise for any other reason other than warranty claims must be in like new condition & subject to a 20% restocking fee. All returns are subject to inspection for determination of full or partial credit. Any returned part that shows evidence of being used or installed contrary to manufacturer's instructions, &/or subjected to improper handling, packaging or return shipping by the customer, will not be eligible for exchange, refund or warranty consideration. All returned electrical items will be inspected & tested. If electrical item is deemed functional, no credit will be issued & item will be returned. All sales are final on discontinued or closeout merchandise.

©2015 KURYAKYN HOLDINGS, LLC ALL RIGHTS RESERVED

KURYAKYN, KURYAKYN K logo and the marks appearing on this instruction sheet are registered and common law trademarks of Kuryakyn Holdings except noted third-party trademarks. A full listing of trademarks and trademark registrations owned by Kuryakyn Holdings can be found at www.kuryakyn.com/legal-notice.

Emissions Notice: The California Air Resources Board (CARB) does not permit the use of aftermarket emission-related parts(s) that alter the performance of OEM emission-related devices unless CARB has issued an Executive Order, other than on racing vehicles on closed courses. Check your local laws and manufacturer's information.

Listed Manufacturers and product model names are for reference only. All product and company names are trademarks or registered trademarks of their respective holders. Use of them does not imply any affiliation with or endorsement by them. All specifications are subject to change without notice.

For additional information on third-party product and company names, please consult our Web page at www.kuryakyn.com/legal-notice